



# VANTEK RUST STOPPER

## PRODUCTION DESCRIPTION

RUST STOPPER stops further erosion and rusting of metal buildings, machinery, tools, vehicles, equipment, boats and virtually all metals. When applied, RUST STOPPER chemically converts rust into a black organic compound. A clear acrylic coating is formed. The coating is sufficient to last for years without painting, or it can be painted-over using solvent-based epoxy, urethane, latex or oil-based paints. Extends the life of anything made of metal.

## RECOMMENDED USES

For use by agricultural buildings, industrial plants, schools, institutions, office buildings, homes, and farms. Use on vehicles, boats, heavy equipment, metal buildings, tools and virtually any metal surface.

## ADVANTAGES

- Oxidizes corrosion and scale
- Non-Flammable
- Brightens surface
- Highly concentrated and powerful

## PRECAUTIONS

- Keep out of reach of children.
- Harmful if swallowed.
- May cause irritation to eyes or skin.
- Do not get in eyes, or on skin or clothing.
- Wash thoroughly after handling.
- Remove contaminated clothing and shoes.
- Wash clothing before reuse.
- Thoroughly clean contaminated shoes.

## TECHNICAL DATA

FEATURE	ADVANTAGE
COLOR	Opaque
ODOR	Mild
VISCOSITY	75 cps @ 25°C
WEIGHT/GALLON	9.07
pH	2.5-3.0
SHELF LIFE	1 year in unopened container

## PACKAGING

- 20 oz. spray (12/case) (#VTK5003)
- 1 qt. (6/case) (#VTK5002)
- 1 gal. (4/case) (#VTK5001)

## COVERAGE

One gallon typically covers up to 500 sq. ft. (General Use)

## LIMITATIONS

- Empty containers may contain product residue, including flammable or explosive vapors. Do not cut, puncture, or weld on or near container.
- All label warnings must be observed until the container has been commercially cleaned or reconditioned.
- Keep out of reach of children.
- Refer to Material Safety Data Sheet for further safety and handling information.
- Dispose of product in accordance with Federal, State and Local regulations. Use licensed hazardous waste company.
- See individual labels for more caution statements.
- See reverse side for limitations of our liability and warranty.



## SURFACE PREPARATION

Remove all debris. Soils, oils, and other contaminants can be removed by high-pressure cleaning with mild degreaser (if needed). Allow it to dry. Clean rusted surface of loose rust flakes (if remaining) with wire brush, pressure wash, or other mechanical means.

## DIRECTIONS

Shake or stir the product well before using. Some phase separation may occur during long term storage, but product quality is not compromised. Thinning is not required. Product can be sprayed, rolled, or brushed. The rust starts to turn black within a few minutes of application. A second coat can be applied to ensure complete conversion of all rust. Allow 30-45 minutes of dry time before applying a second coat. Allow up to 48 hours for complete cure of the rust converter before applying a topcoat. Reseal container immediately after decanting.

## CLEAN UP

Clean tools and equipment with clean water immediately after use. Cured material must be removed mechanically.

## FIRST AID

**In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin, wash thoroughly with soap and water. If swallowed, give water and contact physician.**

## DISPOSAL

Empty containers may contain product residue, including flammable or combustible vapors. Do not cut, puncture, or weld near these containers. Label warnings must be observed until containers have been commercially cleaned or reconditioned. Containers to be thrown out must be disposed of in accordance with federal, state, and local regulations. Use only licensed hazardous waste disposal companies if required.

## LIMITED WARRANTY

Vantek warrants for a period of one (1) year that its products will be free of manufacturing defects and will be in conformity with published specifications when handled, stored, mixed, and applied in accordance with recommendations of Vantek. If any product fails to meet this warranty, the liability of Vantek will be limited to replacement of any non-conforming material if notice of such non-conformity is given to Vantek within (1) one year of delivery of materials. Vantek may in its discretion refund the price received by Vantek in lieu of replacing the material. No customer, distributor, or representative of Vantek is authorized to change or modify the published specifications of this warranty in any way. No one is authorized to make oral warranties on behalf of Vantek. In order to obtain replacement or refund the customer must provide written notice containing full details of the non-conformity. Vantek reserves the right to inspect the non-conforming material prior to replacement. EXCEPT FOR THE EXPRESSED WARRANTY STATED ABOVE, THERE ARE NO OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR PURPOSE. VANTEK'S OBLIGATION SHALL NOT EXTEND BEYOND THE OBLIGATIONS EXPRESSLY UNDERTAKEN ABOVE AND VANTEK SHALL HAVE NO LIABILITY OR RESPONSIBILITY TO THE PURCHASER OR ANY THIRD PARTY FOR ANY LOSS, COST, EXPENSE, DAMAGE OR LIABILITY, WHETHER DIRECT OR INDIRECT, OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.